



Dell™ PowerEdge T30 (E3-1225, 8GB) 30.000 Ден

DELL™ PowerEdge™ T30, 4 x 3.5" SATA HDD Chassis, Intel C236, Intel® Xeon® Processor E3-1225 v5 (3.3GHz, 8MB SmartCache, 4 Cores, 4 Threads), 1x8GB DDR4, 4 DIMM slots; Maximum RAM: Up to 64GB DDR4 2133MT/s ECC, 1TB HDD, Software RAID: Intel Rapid Storage Controller 12.0 (supports SATA 6Gb/s or SATA 3Gb/s), DVD+/-RW SATA Internal, 290W Single Power Supply, Intel I219-LM GbE LAN 10/100/1000 1-port, Intel AMT 11.0, No Operating System, TPM enabled, 3 Years Parts Only Warranty,



Dell™ PowerEdge T130 (E3-1220, 16GB) 67.000 Ден

DELL™ PowerEdge™ T130, Chassis with up to 4, 3.5 Cabled Hard Drives, Intel C236, Intel Xeon E3-1220 v6 3.0GHz, 8M cache, 4C/4T, turbo (72W), 16GB (2 x 8GB) UDIMM, 2400MT/s, Single Rank, x8 Data Width, Up to 64GB (4 DIMM slots): 1GB/2GB/4GB/8GB/16 GB DDR4 up to 1600MHz, 2 x 1TB 7.2K RPM SATA 6Gbps 3.5in Cabled Hard Drive in RAID1 configuration, PERC H330 Integrated RAID Controller - supported Hardware RAID Level 0, 1, 5, 10, 50., DVD+/-RW SATA Internal, Single cabled power supply (290W); European Spare Power Cord 220V, On-Board LOM 1GBE Dual Port (BCM5720 GbE LOM), iDRAC8, Basic, No Operating System, PowerEdge Server FIPS TPM 2.0, 3 Years Parts Only Warranty,



Dell™ PowerEdge T330 (E3-1220, 32GB) 123.000 Ден

Dell™PowerEdge T330, Chassis with up to 8, 3.5" Hot Plug Hard Drives, Intel Xeon E3-1220 v5 3.0GHz, 8M cache, 4C/4T, turbo (80W), 32GB (2 x 16GB) UDIMM, 2400MT/s, Dual Rank, x8 Data Width, 2 x 2TB 7.2K RPM NLSAS 512n 3.5in Hot-plug Hard Drive in RAID 1 configuration, Dual, Hot-plug, Redundant Power Supply (1+1), 495W, DVD-ROM, SATA, Internal, iDRAC8, Basic, On-Board LOM 1GBE Dual Port (BCM5720 GbE LOM), PERC H330 RAID Controller (Supported Hardware RAID Level: 0, 1, 10, 5, 50), 2 x 2M Rack Power Cord C13/C14 12A, PE Server FIPS TPM 1.2v2 CC, Security Bezel, 3 Years Parts only Warranty,



Dell™ PowerEdge R330 (E3-1230, 32GB) 168.795 Ден

Dell™PowerEdge R330, Chassis with up to 4, 3.5" Hot Plug Hard Drives, Intel Xeon E3-1230 v6 3.5GHz, 8M cache, 4C/8T, turbo (72W), 32GB (2 x 16GB) UDIMM, 2400MT/s, Dual Rank, x8 Data Width, 4 x 4TB 7.2K RPM NLSAS 512n 3.5in Hot-plug Hard Drive in RAID 5 configuration, Dual Hot Plug Power Supplies 350W, DVD ROM SATA Internal, iDRAC8, Basic, On-Board LOM 1GBE Dual Port (BCM5720 GbE LOM), PERC H330 RAID Controller (Supported Hardware RAID Level: 0, 1, 10, 5, 50), 2 x C13 to C14, PDU Style, 10 AMP, 6.5 Feet (2m), Power Cord, PE Server FIPS TPM 1.2v2 CC, PCIe Riser, 1x16 PCIe Gen3 FH slot (x8 PCIe lanes) 1x8 PCIe Gen3 LP slot (x4 PCIe lanes), Dell EMC 1U Standard Bezel, ReadyRails Sliding Rails Without Cable Management Arm, 5 Years Parts only Warranty,