



Primacy Simplex Wireless Fire Red

108.000 Ден

- Direct-to-card dye-sublimation/Resin thermal transfer
- Single-sided printing, edge-to-edge
- Standard 300 x 300 dpi resolution
- 32 MB memory (RAM) standard
- Single side: Color (YMCKO): 190 - 225 cards/hour, Monochrome: 800 - 1000 cards/hour
- Dual side: Color (YMCKO-K): 140 cards/hour
- USB (1.0, 1.1, 2.0, 3.0), cable supplied
- Ethernet TCP-IP 10BaseT, 100BaseT (Traffic Led)
- 802.11b/g wireless connection on the Wireless range
- Feeder capacity: 100 cards (0.76 mm – 30 mil)
- Output hopper capacity: 100 cards (0.76 mm – 30 mil)
- Card types: PVC cards, composite PVC cards, PET cards, ABS cards¹, special varnished cards¹
- Card format: ISO CR80 - ISO 7810 (53.98 mm x 85.60 mm)
- Display: Printer LEDs, Graphical notifications from the printer²: cleaning alerts, empty/low level ribbon and card alerts, etc.
- Software: Delivered with Evolis Premium Suite® for Windows®(32/64 bits): XP SP3, Vista, W7, W8, W10, Delivered with a driver for Mac OS X (from 10.6 onwards), Linux OS upon request,



Evolis Primacy Duplex Wireless Fire Red

120.000 Ден

- Direct-to-card dye-sublimation/Resin thermal transfer
- Single-sided printing, edge-to-edge
- Standard 300 x 300 dpi resolution
- 32 MB memory (RAM) standard
- Single side: Color (YMCKO): 190 - 225 cards/hour; Monochrome: 800 - 1000 cards/hour
- Dual side: Color (YMCKO-K): 140 cards/hour
- USB (1.0, 1.1, 2.0, 3.0), cable supplied
- Ethernet TCP-IP 10BaseT, 100BaseT (Traffic Led)
- 802.11b/g wireless connection on the Wireless range
- Feeder capacity: 100 cards (0.76 mm – 30 mil)
- Output hopper capacity: 100 cards (0.76 mm – 30 mil)
- Reject tray/output hopper capacity at the back: 50 cards (0.76 mm – 30 mil)
- Card thickness: 0.25 to 1.25 mm (10 to 50 mil), gauge adjustment (0.25 mm - 10 mil only for monochrome printing)
- Card types: PVC cards, composite PVC cards, PET cards, ABS cards¹, special varnished cards¹
- Card format: ISO CR80 - ISO 7810 (53.98 mm x 85.60 mm)
- Display : Printer LEDs; Graphical notifications from the printer²: cleaning alerts, empty/low level ribbon and card alerts, etc.
- Software: Delivered with Evolis Premium Suite® for Windows®(32/64 bits): XP SP3, Vista, W7, W8, W10, Delivered with a driver for Mac OS X (from 10.6 onwards), Linux OS upon request,



DATACARD-SD360-dual side-ПРОМО

102.500 Ден

- Two-sided (duplex) card printing, Direct-to-card dye-sublimation/resin thermal transfer
- Color and monochrome printing, One- or two-sided, edge-to-edge printing, Full-color and monochrome printing,
- Alphanumeric text, logos and digitized signatures; 1D/2D bar code images, Printer pooling/sharing, UV Printing
- Reloadable supply cartridges with drop-in cleaning roller
- Automatic 100-card input hopper (with exception card slot), and 25-card output hopper
- Optional 200-card input hopper and 100-card output hopper
- SDK support for third-party application development
- Intuitive LCD panel with soft-touch controls
- Optional smart card and magnetic stripe encoding
- Standard Ethernet and USB connectivity
- Power supply : 100-240 Volts AC, 50-60 Hz, 1,8A, 24 Volts DC, 3 A,,

PVC BLANK CARDS - 30MIL

1.000 Ден

CARDS: C4001, PVC BLANK 30MIL - CLASIC RANGE 100pcs,



PVC CardsWhite 30MIL - box of 500pcs

3.460 Ден

PVC CardsWhite 30MIL - box of 500pcs,



ЛАНКом Компјутери д.о.о. Скопје

Булевар Св. Климент Охридски 24
1000 Скопје
Тел: +389 2 329 69 29
Факс: +389 2 322 58 09

Жиро Сметка: 250000000005543
Шпаркасе Банка Македонија АД Скопје
ЕДБ: МК4030994113667
<http://www.lancom.com.mk>
email: infomail@lancom.com.mk

R5F008EAA RIBBON COLOR YMCKO 300

5.300 Ден

RIBBON COLOR YMCKO 300 PRINTS / ROLL *Primacy,

R3011 RIBB COLOR YMCKO 200 IMAGES

3.400 Ден

R3011 RIBBON COLOR YMCKO 200 IMAGES,